

KLB30A/40A ELECTRIC TOW TRACTOR

BRIEF INTRODUCTION OF PRODUCT

- ◎ STEERING WHEEL OPERATION
- ◎ KINLIFT DEDICATED CONTROLLER、ALBRIGHT CONTACTOR、AMP WATER-PROOF CONNECTOR ASSEMBLE
- ◎ STROBE WARNING LIGHT
- ◎ ADJUSTABLE SAFETY SEAT MAKES DRIVING MORE COMFORTABLE AND SAFER

OPTIONAL CONFIGURATION

- ◎ SPECIAL MODEL FOR COLD STORAGE
- ◎ IMPORTED BATTERY
- ◎ HIGH-CAPACITY BATTERY
- ◎ LI-ON BATTERY



ELECTRIC TOW TRACTOR PARAMETERS SHEET

Identification (特征)	品牌 Brand	KINLIFT				
	产品型号 Product model	KLB20A	KLB30A	KLB40A	KLB60A	
weight (重量)	自重 (带标准蓄电池) Truck weight (with battery)(±10%)	kg	665	665	710	1020
	额定牵引力 Rated pulling force (60min rating)	F(N)	500	750	1000	1500
Tyre (轮胎)	轴距 Wheelbase (±5 mm)	y(mm)	1231	1231	1231	1231
	车轮类型 Tyres	Rubber橡胶	Rubber橡胶	Rubber橡胶	Rubber橡胶	Rubber橡胶
Dimension (基本尺寸)	前轮尺寸 Sees of front wheel	Φxw(mm)	3.50-5-6PR	3.50-5-6PR	3.50-5-6PR	3.50-5-6PR
	后轮尺寸 Sizes of rear wheel	Φxw(mm)	4.00-8-6PR	4.00-8-6PR	4.00-8-6PR	4.00-8-6PR
Performance (性能)	额定载重 Max traction weight	Q(kg)	3000	3000	4000	6000
	最大爬坡度, 满载/空载 (5min工作制)	%	7/15	7/15	7/15	7/15
Motor (电机)	驱动电机功率 Drive motor rating	kW	2.5	2.5	4	5
	蓄电池电压/容量 (5小时放电率)	V/Ah	24/210	24/210	48/280	48/280
others (其他)	驱动控制 Type of drive control		AC MEGMEET交流			
	牵引装置 Type of trailer coupling		Latch	Latch	Latch	Latch

ELECTRIC TOW TRACTOR - KLB-B

BRIEF INTRODUCTION OF PRODUCT:

1. IT IS COMFORTABLE AND EASY TO OPERATE BY AN OPERATING HANDLE
2. EPS STEERING SYSTEM ENABLES THE OPERATOR STEER THE TRACTOR WITH LESS FORCE, INCREASING THE SENSITIVITY, IMPROVING THE PERFORMANCE OF STEERING REVERSAL, SO THE TRAVEL SPEED SLOWS DOWN AUTOMATICALLY AS TRAVELLING ON THE CURVE TO MAKE THE OPERATION EASIER AND SAFER.
3. VERTICAL DRIVE OF AC ENGINE IS NO NEED CARBON BRUSH, HAVING A BETTER START FUNCTION AND REGENERATING BRAKING FUNCTION ON THE RAMP, EFFECTIVELY INCREASING THE WORK EFFICIENCY AND SERVICE DURATION OF ELECTRIC ENGINE PLUS MORE ENERGY-SAVING.
4. THE VEHICLE IS CONFIGURED WITH MAIN CONTROLLER OF ZAPI, CONTACTOR OF ALBRIGHT, WATER-PROOF CONNECTOR ASSEMBLY OF ELECTRIC POWER SUPPLY OF AMP

OPTIONAL CONFIGURATION:

1. SPECIAL MODEL FOR A REFRIGERATED STORAGE
2. IMPORTED BATTERY
3. HIGH-CAPACITY BATTERY
4. LI-ON BATTERY
5. PROTECTIVE ARMREST



	MODEL (型号)		KLB30B
Performance (性能)	Maximum load capacity (负载能力)	kg	3000
	Maximum lifting height (起升高度)	H1 mm	280
Dimensions (尺寸)	Service Weight (with battery) (重量含电池)	kg	670
	Overall length of frame (整车长度)	L mm	1467
Tire (轮胎)	Overall width of frame (整车宽度)	B mm	735
	Handle height(手柄高度)	H mm	1410
Electrical components (动力形式)	Min ground clearance(最小离地间隙)	S mm	30
	Wheelbase (轴距)	Y mm	1145
battery (电池)	Minimum turning radius (without platform) (不带踏板最小转弯半径)	Wa mm	1370
	Front wheel (承载轮)	mm	180*55
Performance (性能)	Drive wheel (驱动轮)	mm	230*75
	Minimum turning radius (with platform) (带踏板最小转弯半径)	Wa1 mm	1880
others (其他)	Caster wheel (平衡轮)	mm	130*55
	Wheel material (车轮类型)		Polyurethane(聚氨酯)
Performance (性能)	Drive motor type (驱动电机类型)		AC series motor (交流电机)
	Rated output (功率)	kw	1.5
Performance (性能)	Voltage (电压)	V	24
	Capacity (容量)	AH	210
Performance (性能)	Weight (重量)	kg	195

