

KLJC0806EH .KLJC0806HA



Suitable for single-sided/double-sided pallets



BRIEF INTRODUCTION OF PRODUCT

- ⊙ 240 kg safe working load (2 people)
- ⊙ Non-marking solid tires
- ⊙ Proportional control
- ⊙ Multi-disc brakes
- ⊙ Double flashing working process warning
- ⊙ Dual front wheel drive 0 turning radius
- ⊙ 25% climbing ability
- ⊙ 24V DC power battery, longer battery life
- ⊙ Automatic charging function
- ⊙ Ground and platform power display
- ⊙ Maintenance-free battery
- ⊙ Foldable guardrails for easy transportation and storage
- ⊙ Suitable for indoor decoration, installation, and maintenance work scenes
- ⊙ Equipped with manual emergency descent function
- ⊙ Ground and platform equipped with emergency switches
- ⊙ Control system fault code display
- ⊙ Platform door automatically closes
- ⊙ Automatic deployment of anti-pothole protection system
- ⊙ Tilt sensor monitors working status in real time
- ⊙ Complies with ANSI and OSHA. CE marked, complies with applicable European regulations, including the Machinery Directive using the EN280 design standard
- ⊙ Full fail-safe hydraulic system
- ⊙ Parking automatic brake

STANDARD CONFIGURATION

- ⊙ Battery: Deep cycle power battery
- ⊙ Power supply: 110V or 230V
- ⊙ Control: Engineering grade platform driving handle
- ⊙ Structure: Scissor arm is made of low carbon alloy steel
- ⊙ Platform: Steel checkered plate non-slip tabletop
- ⊙ Painting: After multiple pre-treatment processes, the surface is durable

OPTIONAL CONFIGURATION

- ⊙ Platform work light
- ⊙ Narrow basket for ceiling grid access
- ⊙ Pipe carrying kit
- ⊙ Tool box
- ⊙ Foam cushioning kit
- ⊙ Ground to platform AC power supply
- ⊙ Overload limit

KLJC0806EH .KLJC0806HA Product Parameters

| Model (型号) | | KLJC0806EH | KLJC0806HA | |
|--|--|----------------|----------------------|--------|
| Dimensions (尺寸) | Maximum safe working height(最大安全工作高度) | 7.8 m | 7.8 m | |
| | Maximum platform height(最大平台高度) | A | 5.8 m | |
| | Machine length (including step ladder)(整机长度(含脚踏梯)) | C | 1.85 m | |
| | Overall length (without step ladder)(整机长度(无脚踏梯)) | | 1.69 m | |
| | Machine width(整机宽度) | B | 0.76 m | |
| | Overall height (guardrails extended)(整机高度(护栏展开)) | H | 2.30 m | 2.30 m |
| | Overall height (guardrails folded)(整机高度(护栏折叠)) | | 1.80 m | 1.80 m |
| | Platform width(平台宽度) | F | 0.74m | |
| | Platform length(平台长度) | E | 1.67 m | |
| | Platform extension length(平台延伸长度) | | 0.90 m | |
| | Ground clearance (not lifted)(离地间隙(未起升状态)) | | 0.10 m | |
| | Ground clearance (lifted state)(离地间隙(起升状态)) | | 0.15 m | |
| | Wheelbase(轴距) | D | 1.36 m | |
| | Tire(轮胎) | | Ø 323 × 100 mm | |
| Performance (性能) | Security workloads(安全工作负载) | 240 kg | 240 kg | |
| | Extended platform load(延伸平台负载) | | 110 kg | |
| | Maximum number of passengers(最大乘员数) | | 2 | |
| | Maximum allowable manual force(最大允许手动力) | | 400 N | |
| | Gradeability(爬坡能力) | | 25% | |
| | Maximum allowable machine tilt(最大允许整机倾斜) | | 1.5° / 3° | |
| | Machine weight(整机重量) | 1580 kg | 1595 kg | |
| | Rise time(上升时间) | | 20-25 sec | |
| | Fall time(下降时间) | | 25-30 sec | |
| | Maximum travel speed (lowered/raised)(最大行驶速度(降低/起升)) | 3.5 / 0.8 km/h | 4.0 / 0.5 km/h | |
| | Electrical and hydraulic (电气和液压) | Voltage(电压) | 24V DC | |
| Drive wheel motor(驱动轮电机) | | 3.0 kW | 24V/0.75 kW / 2.2 Kw | |
| Batteries (deep cycle/sealed gel)(蓄电池(深循环/密封凝胶)) | | 150 Ah | 150 Ah | |
| Charger(充电器) | | 24V/30A | | |
| Maximum hydraulic system pressure(最大液压系统压力) | | 225 bar | | |
| Work Pressure(工作压力) | | 170 bar | | |
| Hydraulic oil tank(液压油箱) | | 15 L | 15 L | |
| Hydraulic oil tank(液压油箱) | 5 L | 5 L | | |

